



BAD309E Searchlight

- ◆ Explosion protection to
 - CENELEC
 - IEC
 - NEC
- ◆ Can be used in
 - Zone 2
 - Zone 21 and Zone 22
 - Class I, Zone 2
 - Class I, Division 2, Groups A, B, C, D
- ◆ Safe and reliable: the product with good explosion-proof performance and antistatic effect, can safely and reliably work in various combustible areas.
- ◆ Efficient and energy-saving: LED solid lamp, low energy consumption, high luminous efficacy, long service life, maintenance free and no subsequent usage cost, memory-free battery is recyclable, pollution-free.
- ◆ Water-proof and damage-proof: the light adopts whole-sealing craft, applicable in damp and severe atmosphere, special alloy enclosure makes sure the light can resist strong shock and impact.
- ◆ Intelligent control: the light is with two kinds of working modes: strong light and working light, switch is controlled by intelligent chip, the strong light and weak light can be changed at random, single-chip control; with battery display and special protection circuit, with protection function of anti-over charging, over discharging and short circuit, reliably protect the battery and prolong the service life.
- ◆ Convenient and durable: unique lamp cap; lighting angle can be adjusted within the scope of -45~55, no lighting dead angle (lighting range of strong light: 800m, effective distance: 300m, suitable for long-distance searching and lighting in large area of close range), light weight, portable type, horizontal type, hang type, magnetic absorption, etc, convenient to use; the switch is with anti-incorrect operation function.



Technical data

Searchlight BAD309E

Explosion protection

Gas explosion protection

⊕ II 3 G Ex nR IIC T6 Gc

Dust explosion protection

⊕ II 2 D Ex tb IIIC T80°C Db IP66

Certificates

LCIE 12 ATEX_____

Conformity to standards

EN 60079-0: 2009, EN 60079-15: 2010, EN 60079-31: 2009
IEC 60079-0: 2007, IEC 60079-15: 2010, IEC60079-31: 2008

Rated voltage

12V

Rated capacity

4Ah

Lamp(LED)

Rated power

9W / 3W

Average service life

100000h

Continuous working time

Strong light

≈ 8h

Working light

≈ 18h

Charging time

≈ 8h

Service life of battery

about 1000 times cycling

Degree of protection

IP66

Weight

1.9kg

Zones 2; 21&22